










Nordik Ice Porcelain Floor-Wall Tile

Referencia/Reference: 123032221
Formato/Format: 9.4X47.2 in.
Color: Hielo/Ice



| | | |
|-------------------------------------------------------------------------------------|----------------------------------------|--------------------------------------------|
|  | TRÁFICO TRAFFIC | Comercial General / General Commercial |
|  | ACABADO FINISH | Mate / Matte |
|  | ASPECTO APPEARANCE | Caras Diferenciadas / Differentiated Faces |
|  | M2 POR CAJA SQ FT APPROX | 1,45 15,607655 |
|  | UNIDADES PIECES | 5 |
|  | PESO BRUTO CAJA kg WEIGHT LB APPROX | 22,78 50,22 |
|  | ESPESOR NOMINAL NOMINAL THICKNESS | 10,5 +/-0,3 |
|  | CAJAS POR ESTIBA CARTONS PER PALLET | 32 |
|  | VOLATILE ORGANIC COMPOUNDS | 0 |

El color presentado en la fotografía es una aproximación al color real. The color represented in the photograph is an approximation to the real color.

Floors for use in commercial and institutional areas with an average daily traffic of less than 5,000 people. These floors are also suitable for all residential areas. Important: Do not use for floors in airports, transportation terminals, industries that use heavy machinery, supermarkets and hypermarkets.

Caution: With the exception of Corona ARD® Slip Resistance products, ceramic products decrease their slip resistance when in contact with water. In humid areas, products with a high coefficient of friction are recommended. When removing the pallet straps, it is recommended to be careful at the ends to prevent the boxes from falling. It is advisable to handle the product between two people due to the length and weight of the product.

CHARACTERISTICS, ADVANTAGES AND BENEFITS:

The Nordik Porcelain Tile in matte finish, Ice color and 9.4X47.2 format, is a strip with a design inspired by Oak wood with a smooth grain and homogeneous ice-colored tone, ideal for installation in all areas due to its General Commercial use. Highly realistic design due to its different differentiated faces and microstructure, allowing a greater resemblance to natural wood. Non-rectified product. Installation recommendation: 25% offset, ideal for General Commercial use. It has five (5) differentiated faces (CD), tiles with subtle differences between one piece and another to give greater realism and naturalness to the product. Ultra-resistant to blows, scratches, stains and humidity, it also has Digital Printing technology (HIGH DEFINITION HD).

Garantía Corona | Corona quality guaranteed: 12 Años/Years

Orchid Ceramics
by **corona**

Nordik Ice Porcelain Floor-Wall Tile

| CARACTERÍSTICAS TÉCNICAS TECHNICAL CHARACTERISTICS | | ENSAYO TEST | ESPECIFICACIÓN SPECIFICACION NTC 919 / ISO 13006 | MEDICIONES LOTES PROMEDIO CORONA/ CORONA AVERAGE LOT MEASUREMENTS |
|---------------------------------------------------------------------|----------------------------------------|----------------------------------|--------------------------------------------------------------------|----------------------------------------------------------------------|
| ANCHO Y LARGO LENGHT AND WIDTH | | NTC 4321 - 2 ISO 10545 - 2 | (±) 2.00% del tamaño de fabricación; hasta máximo 5 mm | (±) 2.00% del tamaño de fabricación; hasta máximo 5 mm |
| PLANIRADIDAD DE LA SUPERFICIE SURFACE FLATNESS | Curvatura Central Central Curvature | NTC 4321 - 2 ISO 10545 - 2 | (±) 0.50% de la diagonal del tamaño de fabricación | (±) 0.30% de la diagonal del tamaño de fabricación |
| | Curvatura del lado Edge Curvature | NTC 4321 - 2 ISO 10545 - 2 | (±) 0.50% relativa al correspondiente tamaño de fabricación | (±) 0.30% relativa al correspondiente tamaño de fabricación |
| | Ortogonalidad Warpage | NTC 4321 - 2 ISO 10545 - 2 | (±) 0.50% de la diagonal del tamaño de fabricación | (±) 0.30% de la diagonal del tamaño de fabricación |
| DEFECTOS SUPERFICIALES SURFACE DEFECTS | | NTC 4321 - 2 ISO 10545 - 2 | Mínimo 95% libre de defectos/ Minimum 95% without deffects | Mínimo 95% libre de defectos/ Minimum 95% without deffects |
| ABSORCIÓN DE AGUA WATER ABSORPTION | | NTC 4321 - 3 ISO 10545 - 3 | Máximo 0.50% | Máximo 0.50% |
| RESISTENCIA A LA ROTURA BREAKING STRENGHT | | NTC 4321 - 4 ISO 10545 - 4 | Mínimo 1300 N / Minimum 1300 N | Mínimo 1400 N / Minimum 1400 N |
| MÓDULO DE ROTURA MODULUS OF RUPTURE | | NTC 4321 - 4 ISO 10545 - 4 | Mínimo 35 N/mm2 / Minimum 35 N/mm2 | Mínimo 35 N/mm2 / Minimum 35 N/mm2 |
| RESISTENCIA A LA ABRASIÓN ABRASION RESISTANCE | | NTC 4321 - 7 ISO 10545 - 7 | Informe de cumplimiento de la clase de abrasión y los ciclos | Clase 4 / Class 4 |
| COEFICIENTE DE FRICCIÓN DINÁMICO DYNAMIC COEFFICIENT OF FRICTION | | NTC 4321 - 17 ISO 10545 - 17 | Declarado por el fabricante / Metodo de ensayo disponible | Clase 2/ Class 2 |
| RESISTENCIA AL MANCHADO RESISTANCE TO STAINING | | NTC 4321 - 14 NTC 4321 - 14 | Mínimo clase 3 / Minimum class 3 | Mínimo clase 4 / Minimum class 4 |
| RESISTENCIA A AGENTES QUÍMICOS RESISTACE TO CHEMICALS | | NTC 4321 - 13 NTC 4321-2 - 13 | Mínimo clase B / Mimimum B class | Mínimo Clase A / Mimimum A Class |
| RESISTENCIA AL CHOQUE TÉRMICO THERMAL SHOCK RESISTANCE | | NTC 4321-2 - 9 NTC 4321 - 9 | La indicada por el fabricante/Manufacturer to state classification | Mínimo clase BA / Mimimum BA class |